

KÄRCHER

makes a difference



EFFICIENCY AT THE PUSH OF A BUTTON.

The HDS compact class with eco!efficiency mode.

PROFESSIONAL | HDS 2.3/12 C ED AND HDS 3.0/20 C EA

HDS COMPACT CLASS



It's all in the detail.

Kärcher's German-built electric hot water machines are the most advanced on the market, featuring Kärcher's patented axial pump integrated with a 2-pole motor for optimum efficiency. Kärcher's efficient and compact downdraft-fired burner uses far less fuel than standard heat exchangers. Units come standard with low-fuel shut-off, low-water protection, high-temperature shut-off, thermal overload protection, soft-grip gun, and 50' hose. All units are ETL certified to UL and CSA standards.



1 Efficiency

- ecoefficiency mode – economical and environmentally friendly, even during longer periods of use.
- Reduces fuel consumption and CO₂ emissions by 20%.
- Accurate cleaning agent dosing unit with clear rinse function.

2 Ease of use

- Intuitive operation with large single-button selector switch.
- Easy fillable tanks for fuel and detergent.

3 Storage

- Lockable accessory compartment for nozzles, tools, etc.
- Integrated power cord and spray lance holder.

4 Mobility

- New push bar handle for easier maneuverability and control.
- Robust wheels and steering mechanism for maneuverability.
- Large integrated handles in the chassis.
- Integrated tilting aid for effortlessly negotiating obstacles such as steps and curbs.

Technical data and equipment.

Technical Data

Model	Part No.	GPM	PSI	HP	Electrical	Amps	Pump	Weight (lbs.)	Dimensions (L x W x H) inches
HDS 2.3/12 C Ed	1.272-201.0	2.3	1100	2.8	110-120V/1ph	18.5	Kärcher Axial	270	42 x 26 x 36
HDS 3.0/20 C Ea	1.170-616.0	1.3-2.9	460-2000	5.6	220-240V/1ph	18.5	Kärcher Axial	285	42 x 26 x 36

Accessories

Product	Order No.	Description
100' Pivot Hose Reel	8.750-685.0	100' Pivot Hose Reel, 3/8" x 100' with pin lock
Pivot hose reel bracket mount	8.921-775.0	*requires additional parts below
*Coupler	8.709-531.0	Coupler, Twist Seal, 3/8" Socket, Female
*Street Elbow	9.802-114.0	Street Elbow, 3/8" Mpt x 3/8" Fpt / 90 Degree
*Hose	8.918-280.0	Hose, 3/8" x 6'
Servo Control	4.775-526.0	Servo-press controller, less than 3.3 GPM