

# KÄRCHER

makes a difference



## **RUGGED GASOLINE OR DIESEL- POWERED PRESSURE WASHER.**

Skid mounted and hot water power for commercial use.

# LIBERTY HDS PE/DE CAGE



## Workhorses of the industry.

Kärcher Series oil-fired skids are the workhorses of the pressure washer industry. Delivering up to 5.6 GPM of hot water at up to 3500 PSI, these rugged gas and diesel-powered machines are built on an open frame using heavy-gauge 1-1/4" powder coated steel and are ideal for mounting in a truck or on a trailer. The electric-start engine and powerful belt-drive Kärcher KT pump are isolated from the rest of the machine on a shock-mounted sub-frame to reduce vibration. Steam combination comes standard with all models.



### 1 Powerful and durable

- Reliable, super-duty gasoline-or diesel-powered engines with electric start.
- High-output burner with transformer for years of reliable and affordable operation.
- Industrial-grade, tri-plunger, oil-bath, direct- drive, Kärcher pump with 7-year warranty.
- 50 ft. of durable, wire braid hose with extended guard for burst protection.
- Heavy-gauge 11/4" steel frame with powder coat finish for all-weather protection.
- Power platform cushioned on 8 vibration isolators for smoother operation and long-life protection to frame and components.
- Insulated Schedule 80 heating coils is made of 1/2-inch, coldrolled, steel pipe; with stainless steel wrap and 5-year warranty.
- VRT100 unloader provides a long life span.
- Winco generator proven to function under the most demanding working conditions.

### 2 Smart features

- High pressure rupture disc rated to 7000 PSI to protect user against injury.
- Cast iron pulley system with totally enclosed, OSHA-compliant belt guard, and easy-to-adjust TrueTrak belt tension.
- Insulated, high-pressure trigger gun for hours of fatigue-free cleaning.
- 2.5 gal. float tank for high-pressure application of soap and to prevent pump cavitation.
- Water resistant control box with burner on/off switch, adjustable thermo stat and hour meter.
- Easy and ergonomic access to nozzles.

# Technical data and equipment.

## Technical Data

Model	Part No.	GPM	PSI	CC	Engine	Fuel	Pump	Burner	Weight (lbs.)	Dimensions (L x W x H)
HDS 3.9/30 Pe Cage	1.575-600.0	3.9	3000	389	Honda GX390	Gas	Kärcher KT	12V DC	790	41 x 41 x 41
HDS 4.8/30 Pe Cage	1.575-601.0	4.8	3000	479	Vanguard 16	Gas	Kärcher KT	12V DC	800	41 x 41 x 41
HDS 4.8/30 Pe Cage	1.575-602.0	4.8	3000	479	Vanguard 16	Gas	Kärcher KT	120V AC	945	41 x 41 x 41
HDS 4.7/35 Pe Cage	1.575-603.0	4.7	3500	688	Honda GX630	Gas	Kärcher KT	12V DC	855	41 x 41 x 41
HDS 4.7/35 Pe Cage	1.575-604.0	4.7	3500	688	Honda GX630	Gas	Kärcher KT	120V AC	890	41 x 41 x 41
HDS 5.6/35 Pe Cage	1.575-605.0	5.6	3500	688	Honda GX660	Gas	Kärcher KT	12V DC	852	41 x 41 x 41
HDS 5.6/35 Pe Cage	1.575-606.0	5.6	3500	688	Honda GX660	Gas	Kärcher KT	120V AC	970	41 x 41 x 41
HDS 5.6/35 De Cage	1.110-622.0	5.4	3500	1123	Kubota D1105-E3B	Diesel	Kärcher KT	12V DC	1214	44 x 51 x 41
HDS 5.6/35 De Cage	1.110-623.0	5.4	3500	1123	Kubota D1105-E3B	Diesel	Kärcher KT	120V AC	1300	44 x 51 x 41

## Options (factory installed)

Product name	Order No.	Description
Wheel Kit Assembly	9.801-003.0	Wheel kit assembly (gas engine skid only)
Stackless Flue Adapter	8.903-430.0	Stackless flue adapter

## Options (field installed)

Product	Order No.	Description
Battery	8.904-051.0	Battery installed on Honda GX630 and GX660 models only